



Product: Helix Test System



Article code: 3FSKS630802 - 3FSKS630808

TECHNICAL DATA SHEET 1/2				
Product name:	Art. Code:	Content:	Size:	Material:
Helix Test System 3,5 min-134°C/15min-121°C	3FSKS630802	100 strips	<i>PCD Conform:</i> EN867-5-4.5.7.	<i>Tube:</i> Teflon
Helix Test System 3,5 min-134°C/15min-121°C	3FSKS630804	400 strips	<i>Indicator:</i> Length: 73mm Width: 5mm	<i>Capsule:</i> Polypropylene
Helix Test System 5,3 min-134°C/15min-121°C	3FSKS630806	400 strips	<i>Packaging:</i> Length: 175mm Width: 125mm Height: 20mm	<i>Connections:</i> PP/Teflon
Helix Test System 7,0 min-134°C/20min-121°C	3FSKS630808	100 strips		<i>O-ring:</i> Silicon rubber
				<i>Strips:</i> Wood free offset cardboard of 300gr ² , which is printed in offset.
Intended use:	The Helix Test Systems are intended to test if hollow loads are properly sterilised			
Shelf life:	3 years			
Sterile / Non-sterile:	Non-sterile			
Sterilization method:	Steam			
Resterilization:	No			
Latex free:	Yes			
DEHP free:	Yes			
Single use:	Yes			
Tube wall thickness:	0,5 ±0,025 mm			
Internal tube diameter:	2,0 ±0,1 mm			
Tube length:	1500 ±15 mm			
Capsule mass:	10,0 ±0,1 g			
Free capsule volume:	6 ±1 % of the total volume minus the capsule volume = volume of the tube.			
Material of construction:	PTFE			
CE class:	I			
Standards:	ISO11140-1 (Type-2), EN867-5-4.5.7., EN13060-A1-8.10; EN 285+A2.			
Picture :	<p>ART.Nº. 3FSKS630802 STEAM* DARK 134 °C - 3,5 MIN. / 121 °C - 15 MIN.</p> <p>ART.Nº. 3FSKS630804 STEAM* DARK 134 °C - 3,5 MIN. / 121 °C - 15 MIN.</p> <p>ART.Nº. 3FSKS630806 STEAM* DARK 134 °C - 5,3 MIN. / 121 °C - 15 MIN.</p> <p>ART.Nº. 3FSKS630808 STEAM* DARK 134 °C - 7,0 MIN. / 121 °C - 20 MIN.</p> <p>Helix Test System</p> <p>INTERSTER</p> <p>REF: 3FSKS630802 134 °C - 3,5 min. 121 °C - 15 min. Contents: 100 indicator strips 1 helix tube 1 user manual EN 867-5 EN ISO 11140-1 (Type 2) Manufactured in The Netherlands, www.interster.nl</p>			
Test results:	The indicator has to change from light blue to dark when exposed to steam in appropriate cycle.			
Product family:	The Helix Test Systems are part of the control products family.			
Related products:	3FSKS635801 DPCD-3 Professional			
Storage conditions:	The Helix Test Systems should be stored in dry, cool areas away from sunlight with a temperature range of 10-30°C and a relative humidity of 30-70%.			



Product: Helix Test System

Article code: 3FSKS630802 - 3FSKS630808

TECHNICAL DATA SHEET 2/2	
Date: 09-03-2016  J. Oort Sales Director	Date: 09-03-2016  B. Randshuizen Quality Manager
<p style="text-align: center;">Disclaimer</p> <p>The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed, including without limitation any warranty of merchantability and fitness for use. All users of the material are responsible for assuring that it is suitable for their needs, environment and end use. All data is subject to change as Interster International B.V. deems appropriate. Refer to www.interster.nl for contact information.</p>	

This document replaces all preceding Technical Data Sheets